

Gas cartridge LEO 100 natural gas tunnel

LEO/100/TUNEL/G20

EAN:
5903751012122

Leo tunnel with a panoramic view of the fire, a discreet façade frame and a minimum of external elements makes the fire in the foreground. The Leo series is suitable for natural gas (NG) combustion.



Technical Specifications

Rated output (kW)	9,0
Range of heating power (kW)	4,7 - 9,0
Designed for heat recovery unit	Yes
Fuel type	gaz ziemny
Destination country	at be ch cy cz de dk ee es fi fr gb gr hr ie it lt lu lv no pl pt ro se si sk tr
The energy efficiency index EEI	94,40
Glazing type	straight
Material	steel
Width (cm)	112,90
Height (cm)	83,90
Depth (cm)	43,40

Features

MAXIMUM USE OF ENERGY

An innovative, elegant gas insert with a horizontal and realistic view of fire.

High quality, convenience and simplicity of use.

Undistorted view of fire thanks to concealed frame of the facade and minimal number of visible steel elements.

Specially designed burner provides a realistic view of fire like in a real wood-burning fireplace. Additional flame height adjustment.

SAFETY AT THE HIGHEST LEVEL

The device has a CE certificate, which guarantees the safety of use, protection of health and the environment.

Hermetically closed combustion chamber, which gives the highest degree of safety; In case of any problems with the air-flue gas duct or the gas supply, the fireplace is automatically extinguished.

CONVENIENT USE

Thermostatic control: complete control with a dedicated remote control equipped with thermostat.

Choice of fuel: the insert with a sealed chamber features an option to use either LPG or natural gas as fuel.

Traditional chimney not required - a system of concentric ducts facilitates installation in rooms without a chimney, the ducts just need to be run to the outside, through a wall or roof.

Timer: option to pre-programme a heating schedule even seven days in advance.

No external source of power required (the device has its own power supply). The central unit is powered by 4 x 1.5 volt batteries (a second G 60-ZBE power supply module is optional).

The set includes:

- a gas insert fuelled by natural gas
- fire process control unit with a touch remote control
- decorative ceramic wood for combustion chamber lining

ATTENTION! Before purchasing specify what gas will be used for the fireplace - natural gas or LPG (from cylinders), as the burner and nozzles have to be selected accordingly. Before installation make sure the device is suitable for the gas in place on site. For all crucial gas parameters see fireplace